

Duke HEATSINK™

Product Holding Units

From the World Leader in Product Holding



Patented Duke HEATSINK™ Technology

- Wraps around bottom and sides of pan to allow for even heat distribution
- It uses no water and eliminates product hot & cold spots
- Improves product quality

Improves Serving Efficiency

- Increases holding capacity
- Pass through design allows crews to work both sides



Reduces Costs

- Reduces energy usage
- Increases product yield



Advanced Electronic Controls

- Time decrement settings for each pan
- Displays product and time remaining
- Simple web based programming with flash drive
- Alpha-numeric controls available

Simplified Clean-Up and Maintenance

- Easy to clean - just remove pans & covers and wipe down
- No cracks or crevices to collect debris
- No doors, latches or hinges to break



Your Solutions Partner



Duke HEATSINK™ Product Holding Units



Shipping Weight: 141lbs / 64kg			Width		Height		Depth	
Model	Control	Vol/Amps/Watts/HZ	in	cm	in	cm	in	cm
FWM3-42-120	Both	120V, 13.3A, 1600W, 50/60Hz	21	53.3	22	55.9	16	40.6
FWM3-42-208	Both	208V, 11.5A, 2400W, 50/60Hz	21	53.3	22	55.9	16	40.6
FWM3-42-230	Both	230V, 10.4A, 2400W, 50/60Hz	21	53.3	22	55.9	16	40.6
FWM3-42-240	Both	240V, 10.0A, 2400W, 50/60Hz	21	53.3	22	55.9	16	40.6



Shipping Weight: 125lbs/57kg			Width		Height		Depth	
Model	Control	Vol/Amps/Watts/HZ	in	cm	in	cm	in	cm
FWM3-51-120	Both	120V, 8.3A, 1000W, 50/60Hz	14	36	26¾	68	16	40.6
FWM3-51-208	Both	208V, 7.2A, 1500W, 50/60Hz	14	36	26¾	68	16	40.6
FWM3-51-240	Both	240V, 6.3A, 1500W, 50/60Hz	14	36	26¾	68	16	40.6
FWM3-51-230CE	Both	230V, 6.3A, 1500W, 50/60Hz	14	36	26¾	68	16	40.6



Shipping Weight: 165lbs / 75kg			Width		Height		Depth	
Model	Control	Vol/Amps/Watts/HZ	in	cm	in	cm	in	cm
FWM3-34-208	Both	208v, 11.6A, 2400W, 50/60Hz	37	94.0	17	43.0	16	40.6
FWM3-34-230	Both	230v, 10.4A, 2400W, 50/60Hz	37	94.0	17	43.0	16	40.6
FWM3-34-240	Both	240v, 10.0A, 2400W, 50/60Hz	37	94.0	17	43.0	16	40.6



Shipping Weight: 91lbs / 41kg			Width		Height		Depth	
Model	Control	Vol/Amps/Watts/HZ	in	cm	in	cm	in	cm
FWM3-22-120	Both	120V, 6.7A, 800W, 50/60Hz	21	53.3	12	30.5	16	40.6
FWM3-22-208	Both	208V, 5.8A, 1200W, 50/60Hz	21	53.3	12	30.5	16	40.6
FWM3-22-230	Both	230V, 5.2A, 1200W, 50/60Hz	21	53.3	12	30.5	16	40.6
FWM3-22-240	Both	240V, 5.0A, 1200W, 50/60Hz	21	53.3	12	30.5	16	40.6



Shipping Weight: 141lbs / 64kg			Width		Height		Depth	
Model	Control	Vol/Amps/Watts/HZ	in	cm	in	cm	in	cm
FWM3-24-120	Both	120V, 13.3A, 1600W, 50/60Hz	37	94.0	12	30.5	16	40.6
FWM3-24-208	Both	208V, 11.5A, 2400W, 50/60Hz	37	94.0	12	30.5	16	40.6
FWM3-24-230	Both	230V, 10.4A, 2400W, 50/60Hz	37	94.0	12	30.5	16	40.6
FWM3-24-240	Both	240V, 10.0A, 2400W, 50/60Hz	37	94.0	12	30.5	16	40.6



Shipping Weight: 113lbs / 51kg			Width		Height		Depth	
Model	Control	Vol/Amps/Watts/HZ	in	cm	in	cm	in	cm
FWM3-23-120	Both	120V, 10.0A, 1200W, 50/60Hz	29	73.7	12	30.5	16	40.6
FWM3-23-208	Both	208V, 8.7A, 1800W, 50/60Hz	29	73.7	12	30.5	16	40.6
FWM3-23-230	Both	230V, 7.8A, 1800W, 50/60Hz	29	73.7	12	30.5	16	40.6
FWM3-23-240	Both	240V, 7.5A, 1800W, 50/60Hz	29	73.7	12	30.5	16	40.6



United Kingdom, Ireland, Nordic Countries

Unit 10
Greendale Business Park
Woodbury, Salterton
Exeter, EX5 1EW
Phone: +44 1395 234140
www.dukemfg.com

Paul Stephens
paul.stephens@dukemfg.com
+44 77136 84343

Europe, Middle East, Africa, Russia

Prague Distribution Center:
Vltavska 219
CZ-252 07 Stechovice
Phone: +420 257 741 A86033

United States, Canada

2305 N. Broadway
St. Louis, MO 63102
Toll Free: 800 735 3853
Phone: 314 231 1130
Fax: 314 231 5074